

POWER LIFT (series) PL-15K-RS

Pulze MHE Lithium Battery is a versatile power source known for its high energy density, making it ideal for a range of electronic devices. Its lightweight design enhances portability, making it suitable for compact gadgets and tools. With a long cycle life, it provides numerous charge and discharge cycles, ensuring durability and reliability over time. The battery also features fast charging capabilities, significantly reducing downtime. Safety is a priority, with built-in mechanisms to prevent overcharging and overheating, enhancing user protection. This combination of features makes the Pulze MHE a preferred choice in both consumer electronics and industrial applications. Its efficiency and performance contribute to the growing demand for lithium battery technology.

PERFORMANCE SPECIFICATIONS

| Nominal Voltage | 48 V |
|--|-----------|
| Operating Voltage | 42 - 58 V |
| Rated Power | 20kW |
| Usable Energy ¹ | 19.2kW |
| Continuous Charge | 150A |
| Continuous Discharge | 300A |
| Back up hours | 15hrs |
| Power Module | Inbuilt |
| ¹ Values provided for 25°C (77°F) | |





ENVIRONMENTAL SPECIFICATIONS

 Operating Temperature
 -20°C to 50°C (-4°F to 122°F)

 Recommended Temperature
 0°C to 30°C (32°F to 86°F)

 Storage Conditions
 20°C to 30°C (-4°F to 86°F)

 Up to 95% RH, non-condensing State of Energy (SoE): 25% initial

 Maximum Elevation
 3000 m (9843 ft)

 Environment
 Indoor

 Ingress Rating
 IP56 (Battery & Power Electronics)

Values provided for 25°C (77°F)

MECHANICAL SPECIFICATIONS

| Dimension | 760X465X360 mm | |
|--|---------------------|--|
| Weight ² | 250Kgs | |
| Mounting Options | Floor or wall mount | |
| ² Dimensions and weight differ slightly | | |

²Dimensions and weight differ slightly.

counterbalance will provide space avaiability

 * specification included in this datasheet are subjected to change without notice

PINNACLE LITHIUM POWER

HPULZE┝

